ProLite E2403WS | 24" Wide

The new E-Series 24” display is the latest pioneering product suitable for both Home, Gaming and Business environments. The 1920x1200 pixel panel has the latest TN technology and boasts a 2000:1 Dynamic Contrast Ratio which can be disabled for greater colour accuracy. A brightness of 300cd/m², an extremely fast 2ms response time, the E2403WS is ideal for movies or games plus it is now full HD and incorporates the HMI input for multiple connectivity and all packaged in iiyama’s trademark sleek and stylish design. A HDMI to DVI cable is now included as standard. The display has been tested to meet all of the technical requirements to be Certified for Windows Vista™.

Technical data		
LCD Panel	Panel	TN
	Diagonal	24" (61.2 cm)
	Display area h x w	324 x 518.4 mm
	Response time	2 ms
	Contrast ratio	2000 : 1 DCR
	Brightness	300 cd / m² max
	Viewing zone	horizontal/vertical: 170°/160°; right/left: 85°/85°; up/down: 85°/75°
	Display colour	16.7 Million
	Pixel pitch h x v	0.270 x 0.270 mm
	Native resolution	2,3 MegaPixel (1920 x 1200)
Electronics	Horizontal sync	31-83 KHz
	Vertical sync	56-75 Hz
	Bandwidth	162 MHz
	Input connector	D-Sub, HDMI
	Output connector	headphone connector
	Plug and Play	VESA DDC2B™
	Synchronization	Separate Sync
	Speaker	2 x 2W
	Included accessories	power cable, D-Sub signal cable, audio cable, DVI-HDMI Cable, user manual, stand
	Apple - Mac	All iiyama monitors are compatible with Apple-Macintosh computers
	Controls	On-Screen-Display in 10 languages (GB, F, D, I, ESP, PL, RU, JP, NL, Ch) and 6 Front controls(Auto, Exit/Volume Button, Scroll Down/Contrast Button, Scroll Up/Brightness Button, Menu/Select, Power)
	User controls	brightness, contrast, colour adjust, auto adjust, geometry (horizontal/vertical position, pixel clock, phase), OSD language, OSD position, OSD time out, volume, input select, recall, miscellaneous (sharpness, DDC/CI, Display Information, DCR, OD, Display Mode)
	Driver	Windows 95 / 98 / 2000 / ME / XP / Vista
	Ergonomics	TCO'03, CE, MPR III (prEN50279), ISO13406-2
	Safety	TÜV GS, FCC-B, UL/C-UL, VCCI-B, GOST-R
	Power supply	AC 100-240V, 50/60 Hz
	power supply unit	internal
	Power management	VESA DPMS, ENERGY STAR®
	Power usage	max. 65 W in normal use, max. 2 W in Power management mode
Mechanical	Anti-theft-device	Kensington-lock prepared
	VESA mounting	100 mm
	Tilt angle	20° up, 5° down
	Weight	6.5 kg
	Dimensions w x h x d	566.0 x 458.5 x 191.5 mm

All trademarks and registered trademarks acknowledged. E & O E. Specifications subject to change without notice. All LCD's comply with ISO-13406-2 in connection with pixel defaults.

Megapixel describes the size of your desktop and therefore the amount of information your display can show. A lcd with a physical resolution of 9.2 mega pixels (3840 x 2400) can show 6 times more information than a display with 1.3 mega pixels (1280 x 1024). That means your desktop is about 600 percent bigger.